



ALUMINIUM FLEXIBLE DUCT

Model single layer

Product informations

ALUMINIUM FLEXIBLE DUCT - 10 M

Highly flexible ducting constructed from a 26-micron multiple layer of aluminium and polyester laminate, reinforced with an encapsulated high-tensile carbon steel spiral helix.

Use: Venting, Air Conditioning

Technical Features

COLOR	GREY-ALLUMINIUM
OPERATING TEMPERATURE	-30°C ÷ 140°C
MAX OPERATING PRESSURE	UP TO 2500 PA
MAX AIR VELOCITY	20 M/S
LENGHT	10 M
FIRE REACTION	EN13501: B ₁ S1D0

SKU	DIAMETER	AIR SPEED 8 M/SEC		AIR SPEED 10 M/SEC	
		AIR FLOW M ³ /H	PRESSURE DROP IN PA	AIR FLOW M ³ /H	PRESSURE DROP IN PA



Aluminium flexible duct

65055	Ø 102 MM	250	15	333	24
65056	Ø 127 MM	383	12	368	18
65057	Ø 152 MM	-	-	-	-
65058	Ø 160 MM	575	8	773	14
65060	Ø 204 MM	900	6,5	1151	10,5
65062	Ø 254 MM	1445	4,7	1843	7,5
65063	Ø 305 MM	-	-	-	-

SKU	MODEL	PRICE
00000065055	INSULATED ALUMINIUM FLEXIBLE DUCT - Ø 102 MM	€3.55 VAT EXCLUDED
00000065056	INSULATED ALUMINIUM FLEXIBLE DUCT - Ø 127 MM	€4.6 VAT EXCLUDED
00000065057	INSULATED ALUMINIUM FLEXIBLE DUCT - Ø 152 MM	€5.35 VAT EXCLUDED
00000065058	INSULATED ALUMINIUM FLEXIBLE DUCT - Ø 160 MM	€5.8 VAT EXCLUDED
00000065060	FLEXIBLE PIPE - Ø 203 MM	€7.2 VAT EXCLUDED
00000065062	INSULATED ALUMINIUM FLEXIBLE DUCT - Ø 254 MM	€10.05 VAT EXCLUDED
00000065063	INSULATED ALUMINIUM FLEXIBLE DUCT - Ø 305 MM	€12.45 VAT EXCLUDED

