



Catalogues and Products > Air-Conditioning > Brackets > **Anchor**

ANCHOR

With hex head screw

Product informations

Universal anchor for fastenings on all types of masonry, plasterboard and concrete.

Product features

- particularly suitable in perforated and hollow walls
- thanks to its special shaping, allows expansion in 6 different directions for consistently effective anchorages on all types of masonry
- equipped with a dynamic collar that allows both a flush-wall installation and a through-wall installation
- anti-rotation mechanisms for perfect functionality during tightening

Installation

For proper installation of the anchor, drill the hole perpendicular to the support with a drill bit of the appropriate diameter. The hole should be cleaned of drilling dust before applying the anchor; it is recommended not to use roto-percussion when drilling the hole on a wall with perforated brick so as not to break the internal bulkheads. Insert the anchor and carry out the desired installation.

Technical Features



Anchor

ANCHOR MATERIAL	SCREW MATERIAL	MINIMUM DRILLING DEPTH	MAXIMUM FIXABLE THICKNESS	A	S	H	R
POLYAMIDE 6	7-8 ØM ELECTROGALVANIZED TREATED STEEL	65 MM	15 MM	8,4X16X1,6 MM	50 MM	7X70 MM	10 MM

SKU	MODEL	PRICE
00000011885	ANCHOR WITH HEX HEAD SCREW	€2.0 VAT EXCLUDED

