



BRASS SOLENOID VALVE FOR GAS

Normally closed with manual reset under voltage, max. pressure 500 mbar and/or 6 bar

Product informations

Normally closed solenoid valve for gas with manual reset; *it can be reset only in the presence of mains voltage and only when the gas detector does not give any danger signals.*

NB. the valve will not open by simply powering the coil, you must manually press the reset mechanism.

Technical Features

USE	NOT AGGRESSIVE GASES OF THE THREE FAMILIES (DRY GASES)
ROOM TEMPERATURE	- 20°C ÷ + 60°C
SUPPLY VOLTAGES	230 V 50 - 60 HZ (ONLY SINGLE-PHASE, THE DEVICE DOES NOT WORK IF POWERED WITH THREE-PHASE VOLTAGE)
ELECTRICAL WIRING	STRAIN RELIEF M20 X 1.5
ABSORBED POWER	230 V = 9 VA
MAXIMUM WORKING PRESSURE	500 MBAR AND 6 BAR
CLOSING TIME	< 1 S
DEGREE OF PROTECTION	IP65 (PROTECTED AGAINST JETS OF WATER PUMPED FROM ANY DIRECTION AND COMPLETELY HERMETIC AGAINST DUST AND FUMES)
MATERIALS	BRASS



Brass Solenoid Valve for Gas

MECHANICAL STRENGTH	GROUP 2
CLASS	A
CONNECTIONS	1/2" FF - 3/4" FF - 1" FF
COMPLIANCE	• REGULATION (EU) 2016/426 (APPLIANCES THAT BURN GASEOUS FUELS) • PED DIRECTIVE 2014/68/EU (VERSION WITH P.MAX 6 BAR) • EMC DIRECTIVE 2014/30/EU • LVD DIRECTIVE 2014/35/EU • ROHS II DIRECTIVE 2011/65/EU

SKU	MODEL	PRICE
00000050370	SOLENOID VALVE FOR GAS - 1/2" FF - 500 MBAR	€125.45 VAT EXCLUDED
0000050370A	SOLENOID VALVE FOR GAS - 3/4" FF - 500 MBAR	€125.45 VAT EXCLUDED
0000050370B	SOLENOID VALVE FOR GAS - 1" FF - 500 MBAR	€150.3 VAT EXCLUDED
000050370/6	SOLENOID VALVE FOR GAS - 1/2" FF - 6 BAR	€127.4 VAT EXCLUDED
00050370A/6	SOLENOID VALVE FOR GAS - 3/4" FF - 6 BAR	€127.4 VAT EXCLUDED
00050370B/6	SOLENOID VALVE FOR GAS - 1" FF - 6 BAR	€152.55 VAT EXCLUDED

