



Catalogues and Products > Air-Conditioning > Condensate Discharge Accessories > **Centrifugal Pump with High Flow Rates**

## CENTRIFUGAL PUMP WITH HIGH FLOW RATES

Flowtank model

### Product informations

**FLOWTANK**, the centrifugal pump with high evacuation flow rates, designed for application in showcases, refrigerated counters and air conditioners with or without a collection tank, where the condensation water is particularly full of impurities.

### Product features

- reversible tank that allows the installation of the pump in all configurations and compact for easy accommodation in small spaces
- with input adapter to avoid all problems of connecting the boiler to the pump
- high performance
- universal, disconnectable electrical connection for easy installation and maintenance

### The kit includes

- FLOWTANK centrifugal pump
- power/alarm cable
- outlet adapter Ø 6/9 mm
- screws and plugs

### Technical Features

|              |                  |
|--------------|------------------|
| POWER SUPPLY | 230 V 50 HZ 65 W |
|--------------|------------------|



## Centrifugal Pump with High Flow Rates

|                                             |                                                                                                                         |
|---------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| <b>MAXIMUM FLOW RATE</b>                    | 800 L/H                                                                                                                 |
| <b>MAX DISCHARGE</b>                        | 5,6 M                                                                                                                   |
| <b>TANK</b>                                 | 1,2 L                                                                                                                   |
| <b>MAXIMUM TEMPERATURE OF THE LIQUID</b>    | 60°C                                                                                                                    |
| <b>PH RESISTANCE</b>                        | > 2,5                                                                                                                   |
| <b>DEGREE OF PROTECTION</b>                 | IP24 (SPLASH-PROOF)                                                                                                     |
| <b>ALARM</b>                                | INTEGRATED                                                                                                              |
| <b>OUTLET DIAMETERS</b>                     | <ul style="list-style-type: none"> <li>• ORIGINAL OUTLET FOR PIPE 9/12 MM</li> <li>• REDUCER FOR PIPE 6/9 MM</li> </ul> |
| <b>NON-RETURN VALVE REMOVABLE IN ¼ TURN</b> |                                                                                                                         |
| <b>PUMP DIMENSIONS</b>                      | 280X130X129 MM (BXDXH)                                                                                                  |

| SKU         | MODEL         | PRICE               |
|-------------|---------------|---------------------|
| 00000011907 | FLOWTANK PUMP | €197.3 VAT EXCLUDED |





## Centrifugal Pump with High Flow Rates

