



THERMAL ACTIVATED SAFETY DEVICE

For gas systems

Product informations

Safety device designed to block the flow of gas and prevent it from leaving the distribution network in the event of fire, its activation take place between 90°C and 100°C and its function is guaranteed at 650°C for 30 minutes.

Technical Features

SKU	CONNECTION	OPERATING PRESSURE	OPERATING TEMPERATURE	INTERVENTION TEMPERATURE	WORK APPLICATION	HEAT RESISTANCE	DIMENSIONS
4296	1/2" FF	MOP 5	- 20°C ÷ + 60°C	100°C - 5K	FOR ALL TYPES OF GAS AS SPECIFIED IN EN 437 AND DVGW G260/1	HTB GT 5 650°C X 30'	L 55 MM
4297	3/4" FF						L 61 MM
4298	1" FF						L 69 MM

SKU	MODEL	PRICE
00000004296	THERMAL ACTIVATED SAFETY DEVICE - 1/2" FF CONNECTIONS	€34.3 VAT EXCLUDED
00000004297	THERMAL ACTIVATED SAFETY DEVICE - 3/4" FF CONNECTIONS	€49.85 VAT EXCLUDED
00000004298	THERMAL ACTIVATED SAFETY DEVICE - 1" FF CONNECTIONS	€70.9 VAT EXCLUDED



Thermal Activated Safety Device

