



FLOAT SWITCH WITH COUNTERWEIGHT

For white waters

Product informations

Float level regulator insensitive to humidity and condensation, designed to activate the connected equipment (pumps, sirens, etc..) when a set level is reached.

Product features

- watertight up to 100 m depth with electric contacts and microswitch / commutator
- micro-switch switch
- injection of non-hygroscopic closed-cell polyurethane foam, which eliminates any residual air inside the regulator body and hermetically seals the regulator itself
- **mercury free**
- equipped with a 110 g counterweight

Technical Features

<i>OPERATING VOLTAGE</i>	230 VAC 50 HZ
<i>RATED VOLTAGE MAX</i>	10 (4) A 250V A.C.
<i>MAX PRESSURE</i>	10 BAR
<i>ELECTRIC CONTACT</i>	SPDT COM + N.C. + N.O
<i>WORK ANGLE</i>	30°



Float Switch with Counterweight

DEGREE OF PROTECTION	IP68 (PROTECTED AGAINST PROLONGED IMMERSION IN WATER AND COMPLETELY HERMETIC AGAINST DUST AND FUMES)
WATER TEMPERATURE	45°C
MATERIAL	• OUTER BODY: ONE-PIECE PRESSURE-BLOWN POLYETHYLENE • INTERNAL CHAMBER: SINGLE PIECE BLOW-MOULDED FOR THE MICROSWITCH SEAT • SPHERE: STAINLESS METAL • CABLE: PVC
DIMENSIONS	172 X 80 X 56 MM (HXWXD)

SKU	MODEL	PRICE
00000070170	FLOAT SWITCH - CABLE 3 M	€29.8 VAT EXCLUDED
00000070171	FLOAT SWITCH - CABLE 5 M	€37.1 VAT EXCLUDED
00000070172	FLOAT SWITCH - CABLE 10 M	€55.3 VAT EXCLUDED





Float Switch with Counterweight

