



DOUBLE LINE REDUCTION GROUP FOR LPG

Version 1ST Stage with/without OPSO shut-off valve, flow rate 500 kg/h

Product informations

Double line reduction group for LPG version **1ST Stage** with/without OPSO shut-off valve, consisting of two identical lines, one service and one relief line.

STRUCTURE OF THE REDUCTION GROUP	
1	BALL VALVE
2	REGULATOR
3	BUTTERFLY VALVE
4	CONDENSATE TANK
5	PRESSURE GAUGE
6	DISCHARGE BALL VALVE
7	RELIEF VALVE
8	NEEDLE TAP
9	SQUARE BALL VALVE
10	MAX PRESSURE SHUT-OFF VALVE - <i>PRESENT ONLY IN SKU 13042</i>

Technical Features

FLOW RATE	500 KG/H
-----------	----------



Double Line Reduction Group for LPG

<i>INLET CONNECTION</i>	DN 40
<i>OUTLET CONNECTION</i>	DN 65
<i>INLET PRESSURE</i>	2 ÷ 18 BAR
<i>OUTPUT PRESSURE</i>	0.5 BAR
<i>TYPE OF REGULATOR</i>	ALFA 40 MODEL
<i>GAUGE TYPE</i>	Ø 60 - 1/4" RADIAL CONNECTION
<i>BUTTERFLY VALVE</i>	DN 65 - PN 16
<i>DISCHARGE BALL VALVE</i>	1/4" CONNECTION - PN 16
<i>SAFETY VALVE CONNECTION</i>	1/4"
<i>SQUARE BALL VALVE</i>	1/2" - PN 16 CONNECTION
<i>BALL VALVE</i>	DN 40 - PN 40
<i>CONDENSATE TANK DIAMETER</i>	Ø 6"
<i>MAX PRESSURE SHUT-OFF VALVE</i>	OPSO - <i>PRESENT ONLY IN SKU 13042</i>
<i>NEEDLE TAP</i>	1/4" - PN 40

SKU	MODEL	PRICE
00000013041	DOUBLE LINE REDUCING GROUP FOR LPG 1 ST STAGE - FLOW RATE 500 KG/H	€8127.65 VAT EXCLUDED
00000013042	DOUBLE LINE REDUCING GROUP FOR LPG 1 ST STAGE - FLOW RATE 500 KG/H - WITH OPSO SHUT-OFF VALVE	€9300.7 VAT EXCLUDED



Double Line Reduction Group for LPG

