



INSULATED 2-PLY PVC FLEXIBLE DUCT

Double wall model

Product informations

Made of reticular tissue in polyester fibers and pvc. Inside duct made of polyolefin resin film and frame of harmonic steel wire built-in between two thermo welded plies.

Insulating polyester fiber.

Outside cover in polyolefin resin leaf.

Technical Features

<i>COLOR</i>	BLACK
<i>OPERATING TEMPERATURE</i>	0°C ÷ + 80°C
<i>BENDING RADIUS</i>	0,8 VAULT THE DIAMETER
<i>MAXIMUM WORKING PRESSURE</i>	2000 PA
<i>MAXIMUM AIR SPEED</i>	20 M/S
<i>LENGTH</i>	10 M
<i>INTERNAL WALL THICKNESS</i>	150 MICRON



Insulated 2-ply pvc flexible duct

SKU	DIAMETER	AIR SPEED 8 M/SEC		AIR SPEED 10 M/SEC	
		AIR FLOW M ³ /H	PRESSURE DROP IN PA	AIR FLOW M ³ /H	PRESSURE DROP IN PA
65005	Ø 160 MM	575	8	773	14

SKU	MODEL	PRICE
00000065005	INSULATED DOUBLE LAYER PVC FLEXIBLE PIPE - Ø 160 MM	€20.65 VAT EXCLUDED

