



LEVEL INDICATOR WITH PIN SEAL

Equipped with PN 10 pin lock with male connection

Product informations

Level indicator generally installed outside tanks, or in any container requiring inspection of the level of the liquid contained in it, so as to intervene if necessary with the appropriate filling; its operation is very simple and uses the principle of communicating vessels, in this way the reading of the level is absolutely faithful to the real level of liquid present in the tank.

Product features

- to fulfill the function for which the level indicator is built, the pipe used to display the liquid level must be transparent
- it is made up of two parts: an upper one which performs the function of intercepting the liquid, connected to a transparent pipe and a lower one which, in addition to intercepting the liquid and connecting it to the aforementioned pipe, includes a tap for discharging the liquid contained in the tube
- its pin closure allows you to isolate the transparent tube to make a quick replacement in case of breakdowns, while the tap located in the lower part of the pair of indicators has the function of draining the liquid still present in the transparent pipe

Technical Features

MAX WORKING PRESSURE	10 BAR
MAX WORKING TEMPERATURE	80°C



Level Indicator with Pin Seal

COMPATIBLE FLUIDS	CONF. UNI 8065 § 6
THREADING	THREAD ACCORDING TO ISO 228/1
MATERIALS	UNIT AND OTHER COMPONENTS: BRASS
DIMENSIONS	• 100 X 75 MM (LXH) - SKU 70010 • 104 X 78 MM (LXH) - SKU 70011 • 108 X 81 MM (LXH) - SKU 70012
PIPE DIMENSIONS	• Ø 10 - L 2000 MM (SKU 70015) • Ø 13 - L 2000 MM (SKU 70016) • Ø 16 - L 2000 MM (SKU 70017)

BUYING GUIDE		
SKU	CONNECTION DIAMETER	PIPE DIAMETER
70010	1/4"	Ø 10 MM
70011	3/8"	Ø 13 MM
70012	1/2"	Ø 16 MM

SKU	MODEL	PRICE
00000070012	LEVEL INDICATOR - 1/2"	€79.05 VAT EXCLUDED
00000070016	TRANSPARENT PIPE - Ø 13 - L 2000 MM	€51.0 VAT EXCLUDED
00000070017	TRANSPARENT PIPE - Ø 16 - L 2000 MM	€69.65 VAT EXCLUDED



Level Indicator with Pin Seal

