



MOTORIZED ZONE VALVE WITH THREE-WAY MICRO

For heating and/or air conditioning

Product informations

Zone valve designed for application in closed circuit cooling and heating water systems, equipped with manual open/close control with metal lever. The use of this valve is not recommended in systems that have substantial reclaimed water (open systems).

Syncron motor, spare for zone valves and actuators, fully insulated and waterproof with built-in reducer.

Technical Features

POWER SUPPLY	230 VAC (24 VAC)
WORKING TEMPERATURE OF FLUIDS	0°C ÷ 90°C
OPERATING AMBIENT TEMPERATURE	0°C ÷ 40°C
CLOSING / OPENING TIME	• ACTIVATION TIME FROM 10 TO 15 SECONDS • SPRING RETURN 4 AND 5 SECONDS
OPERATING PRESSURE	300 PSI / 2 BAR / 2.0 MPA
MATERIALS	• ACTIVATOR: SUPPORT BASE IN STAINLESS STEEL • LID: ALUMINUM • VALVE UNIT: FORGED BRASS • GASKET: NBR



Motorized Zone Valve with Three-Way Micro

SKU R02275 / R05576	
POWER SUPPLY	• 220 VAC 50 HZ (SKU R02275) • 24 VAC 50 HZ (SKU R02276)
ABSORBED POWER	6.5 W, 7 VA
GEARBOX EXIT DIRECTION	COUNTERCLOCKWISE ROTATION
WORKING TEMPERATURE	• FLUID: 0°C ÷ 90°C • ENVIRONMENT: 0°C ÷ 40°C

ORDER GUIDE				
SKU	CONNECTION	KV (CV) FACTOR	CLOSED - OFF P(MPA)	WEIGHT
R05296	1/2" FF	2.6 (3.0)	0.18	750 G
R05297	3/4" FF	3.4 (4.0)	0.16	900 G
R05298	1" FF	6.5 (7.5)	0.14	1050 G

SKU	MODEL	PRICE
00000R05296	MOTORIZED ZONE VALVE - 1/2" FF	€65.5 VAT EXCLUDED
00000R05297	MOTORIZED ZONE VALVE - 3/4" FF	€81.4 VAT EXCLUDED
00000R05298	MOTORIZED ZONE VALVE - 1" FF	€95.3 VAT EXCLUDED



Motorized Zone Valve with Three-Way Micro

