



PERISTALTIC PUMP PE 5200

For condensate drain

Product informations

Peristaltic pump PE 5200 used for the discharge of condensate full of impurities and intended for applications where the quantity of condensate is modest; operated via the 3-level float detection block. Its alarm contact is normally closed, and allows the air conditioning compressor or a solenoid valve to be automatically stopped when the safety level is reached

Product features

- compact design
- the replaceable head and easy-to-access tube, reduce maintenance costs
- low sound level
- 3 function levels - Start / Stop / Safety contact

The kit includes

- **PE 5200** peristaltic pump
- power cable: 1,7 m, 2 thread
- safety contact cable: 1,7 m, 2 thread
- sliding plastic plate, easy to assemble
- float detection block
- detection block installation kit: sleeve Ø 15 x 35 mm - breather pipe Ø int 4 x L. 75 mm - mounting guide - adhesive for fixing



Peristaltic Pump PE 5200

Technical Features

POWER SUPPLY	230 V 50 HZ 11 W
MAXIMUM FLOW RATE	6 L/H
MAX. ASPIRATION HEIGHT	2 M
MAX DISCHARGE	12 M
SOUND LEVEL TO 1 M	≤ 30 DB(A)
SAFETY SWITCH	NF 8 RESISTIVE - 250 V
DETECTION LEVELS	• ON: 16 MM • OFF: 11 MM • SAFETY: 19 MM
DEGREE OF PROTECTION	IP65 (COMPLETELY HERMETIC AGAINST DUST AND FUMES, PROTECTED AGAINST JETS OF WATER FROM ANY DIRECTION)
PUMP BLOCK DIMENSIONS	109 X 110 X 91 MM (LXDXH)
DETECTION BLOCK SIZE	55 X 38 X 37,5 MM (LXDXH)

SKU	MODEL	PRICE
00000011916	PERISTALTIC PUMP PE 5200	€450.35 VAT EXCLUDED





Peristaltic Pump PE 5200

