



## PVC T JOINT

For condensate drain system

### Product informations

T joint with FFF connections in rigid white PVC (RAL 9010) stabilized against UV rays, shockproof and self-extinguishing; it can be used both on sight and under trace.

Pipe and accessories must be fixed together using the O-rings already mounted and/or the special glue.

### Technical Features

|                            |                                                                                                                                                                                    |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>AVAILABLE DIAMETERS</b> | <ul style="list-style-type: none"> <li>• T - FFF Ø 20 MM - <b>SKU 62015</b></li> <li>• T - FFF Ø 25 MM - <b>SKU 62016</b></li> <li>• T - FFF Ø 32 MM - <b>SKU 62017</b></li> </ul> |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

| SKU         | MODEL                 | PRICE              |
|-------------|-----------------------|--------------------|
| 00000062015 | T JOINT - FFF Ø 20 MM | €3.1 VAT EXCLUDED  |
| 00000062016 | T JOINT - FFF Ø 25 MM | €3.45 VAT EXCLUDED |
| 00000062017 | T JOINT - FFF Ø 32 MM | €3.7 VAT EXCLUDED  |



## PVC T Joint

