



## QUICK SEALANT

For hydraulic and pneumatic connection

### Product informations

Anaerobic sealant for metals with medium mechanical strength, seals hydraulic and pneumatic connection, gas, water, GPL, hydrocarbons, oils and various chemical agents.

### Product features

- intermediate fixing
- highly resistant to temperature, corrosion, shocks and vibrations

**NB.** To seal PVC, PP or Nylon fittings, **use only P.T.F.E. based sealant** (SKU 50950 / 50951) by **pre-treating** the plastic threads with **the activator** (SKU 50959), **screw and tighten within 1 minute** (longer waiting times can break the sealant film that is already forming. **Do not use the thread sealer** on ABS and polycarbonate threads, for other types of materials ask in advance for our technical opinion.

### Technical Features

| MAX Ø FOR USE 3/4" - CLEARANCE 0,15 MM |                           |
|----------------------------------------|---------------------------|
| COLOR                                  | BROWN                     |
| SURVEY                                 | FLUORESCENT IN BLUE LIGHT |
| FLASH POINT                            | > + 100°C                 |



## Quick Sealant

|                                  |                  |
|----------------------------------|------------------|
| <b>MANIPULATION</b>              | 10 - 20 MINUTES  |
| <b>FUNCTIONAL HARDENING TIME</b> | 1 - 3 HOURS      |
| <b>FINAL HARDENING TIME</b>      | 3 - 6 HOURS      |
| <b>TEMPERATURE RANGE</b>         | - 55°C ÷ + 150°C |

| SKU         | MODEL                       | PRICE              |
|-------------|-----------------------------|--------------------|
| 00000050956 | FAST SEALANT 53-14 - 250 ML | €83.2 VAT EXCLUDED |

