



Clip-On Regulator and M Left Coupling Adapter

Catalogues and Products > Heating > Lpg regulators for domestic use, high and low pressure > **Clip-On Regulator and M Left Coupling Adapter**

CLIP-ON REGULATOR AND M LEFT COUPLING ADAPTER

Model with fixed and/or external setting, flow rate 1,1 kg/h

Product informations

Clip-on low pressure regulator, designed to make the gas pressure at the outlet of a tank suitable for the downstream user.

Also available the M left coupling adapter Ø 22 mm (sku 1520).

Technical Features

TYPES OF GAS	LPG
FLOW RATE	1,1 KG/H
OPERATING TEMPERATURE	- 20°C ÷ + 50°C
INLET PRESSURE	0,2 ÷ 16 BAR
OUTLET PRESSURE	• 20 ÷ 40 MBAR (SKU 1500) - EXTERNAL SETTING • 30 MBAR (SKU 1510 / 1550) - FIXED SETTING
CONNECTIONS	• INLET: INLET: Ø 24,5 MM (SKU 1500) - Ø 22 MM (SKU 1510) - Ø 20 MM (SKU 1550) • OUTLET: HOSE NOZZLE

SKU	MODEL	PRICE
00000001500	LOW PRESSURE CLIP-ON REGULATOR - EXTERNAL SETTING 20 ÷ 40 MBAR - FLOW RATE 1,1 KG/H	ON REQUEST



Clip-On Regulator and M Left Coupling Adapter

SKU	MODEL	PRICE
00000001510	LOW PRESSURE CLIP-ON REGULATOR - FIXED SETTING 30 MBAR - FLOW RATE 1,1 KG/H	€35.45 VAT EXCLUDED
00000001520	COUPLING ADAPTER Ø 22 MM	€32.55 VAT EXCLUDED
00000001550	LOW PRESSURE CLIP-ON REGULATOR - FIXED SETTING 30 MBAR - FLOW RATE 1,1 KG/H	ON REQUEST

