



Catalogues and Products > Heating > Methane/lpg Regulators for Civil - Industrial Applications > **Low Pressure Regulator**

LOW PRESSURE REGULATOR

Alfa 10 BP series, with balanced direct action regulation

Product informations

Alfa 10 BP series regulator with balanced direct action, equipped with external sensing line and safety relief valve; suitable for the use of not corrosive gases as methane and LPG.

Also available the version with minimum and maximum pressure shut-off valve downstream (sku 2412).

REGULATOR STRUCTURE	
1	O-RING
2	O-RING
3	O-RING
4	O-RING
5	O-RING
6	O-RING
7	O-RING
8	O-RING
9	O-RING
10	MEMBRANE



Low Pressure Regulator

REGULATOR STRUCTURE	
11	PILL
12	LIP RING
13	BALANCING MEMBRANE
A	PLASTIC CAP + O-RING
B	COMPLETE HEADER
C	FULL LEVERAGE
D	COMPLETE BLOCK
E	SHUTTER SEAT + O-RING
F	BOTTOM PLATE + O-RING + SCREWS
G	MEMBRANE PROTECTIVE PLATE
H	• RED SPRING Ø 2 (SETTING 30 ÷ 43 MBAR) • YELLOW SPRING Ø 2,2 (SETTING 42 ÷ 72 MBAR) • BLUE SPRING Ø 2,5 (SETTING 70 ÷ 110 MBAR)
I	ADJUSTMENT FERRULE

Technical Features

FLOW RATE	SEE TABLE UNDERLYING
INLET CONNECTION	1"
OUTPUT CONNECTION	1"
INLET PRESSURE	0,5 ÷ 5 BAR
OUTPUT PRESSURE	16 ÷ 110 MBAR
STANDARD OUTPUT PRESSURE	ON REQUEST
WORKING TEMPERATURE	- 20°C ÷ + 60°C



Low Pressure Regulator

EXTERNAL SENSING LINE	Ø 10
MATERIALS	• BODY: GS 400 CAST IRON • HEADER: DIE-CAST ALUMINIUM • SEAL: NITRILE RUBBER NBR OR HNBR • MEMBRANE: SANDWICH RUBBERIZED FABRIC
DIMENSIONS	180 X 100 X 50 MM

FLOW RATE TABLE M ³ /H		INLET PRESSURE			
		0,3 BAR	0,5 BAR	0,8 BAR	1 BAR
OUTLET PRESSURE	25 MBAR	33 M ³ /H	41 M ³ /H	55 M ³ /H	82 M ³ /H
	35 MBAR	32 M ³ /H	40 M ³ /H	54 M ³ /H	81 M ³ /H
	50 MBAR	30 M ³ /H	39 M ³ /H	53 M ³ /H	80 M ³ /H
	100 MBAR	23 M ³ /H	36 M ³ /H	51 M ³ /H	79 M ³ /H

To obtain the LPG flow rates in kg/h, multiply the values in red by 1,42.

SKU	MODEL	PRICE
00000002410	ALFA 10 BP SERIES REGULATOR - 1"X1" CONNECTION	€565.6 VAT EXCLUDED
00000002412	ALFA 10 BP SERIES REGULATOR - 1"X1" CONNECTION - WITH BLOCK	€963.6 VAT EXCLUDED



Low Pressure Regulator

