



Catalogues and Products > Riscaldamento > Regolatori Metano/gpl per Applicazioni Civili - Industriali > **Low Pressure Regulator**

LOW PRESSURE REGULATOR

Alfa 60 BP series, with balanced direct action regulation

Product informations

Alfa 60 BP series regulator with balanced direct action, equipped with internal sensing line, suitable for the use of not corrosive gases as methane and LPG.

Also available the version with minimum and maximum pressure shut-off valve downstream (sku 2618).

Technical Features

FLOW RATE	SEE TABLE UNDERLYING
INLET CONNECTION	DN 50
OUTPUT CONNECTION	DN 50
INLET PRESSURE	0,5 ÷ 5 BAR
OUTPUT PRESSURE	16 ÷ 320 MBAR
STANDARD OUTPUT PRESSURE	ON REQUEST
WORKING TEMPERATURE	- 20°C ÷ + 60°C
EXTERNAL SENSING LINE	Ø 14
MATERIALS	• BODY: GS 400 CAST IRON • HEADER: STEEL • SEAL: NITRILE RUBBER NBR OR HNBR • MEMBRANE: SANDWICH RUBBERIZED FABRIC



Low Pressure Regulator

DIMENSIONS	540 X 254 X 110 MM
-------------------	--------------------

FLOW RATE TABLE M ³ /H	INLET PRESSURE		
	0,3 BAR	0,5 BAR	1 BAR
25 MBAR	730 M ³ /H	965 M ³ /H	1435 M ³ /H
50 MBAR	705 M ³ /H	950 M ³ /H	1427 M ³ /H
100 MBAR	645 M ³ /H	905 M ³ /H	1412 M ³ /H
150 MBAR	570 M ³ /H	875 M ³ /H	1395 M ³ /H
200 MBAR	477 M ³ /H	826 M ³ /H	1375 M ³ /H
300 MBAR	-	700 M ³ /H	1325 M ³ /H

OUTLET PRESSURE

To obtain the LPG flow rates in kg/h, multiply the values in red by 1.42.

SKU	MODEL	PRICE
00000002616	ALFA 60 BP SERIES REGULATOR - DN 50 - DN 50 CONNECTION	€5027.4 VAT EXCLUDED
00000002618	ALFA 60 BP SERIES REGULATOR - DN 50 - DN 50 CONNECTION - WITH BLOCK	€6409.95 VAT EXCLUDED



Low Pressure Regulator

