



Catalogues and Products > Riscaldamento > Regolatori Gpl Alta e Bassa Pressione per Applicazioni Civili-industriali > **Low Pressure Regulator**

LOW PRESSURE REGULATOR

Model with safety relief valve incorporated, flow rate 60 and/or 120 kg/h

Product informations

Low pressure regulator for LPG with safety relief valve incorporated, designed to make the gas pressure at the outlet of a tank suitable for the downstream user.

Technical Features

TYPES OF GAS	LPG
FLOW RATE	• 60 KG - SKU 1200 • 120 KG - SKU 1205
OPERATING TEMPERATURE	- 20°C ÷ + 50°C
INLET PRESSURE	0,5 ÷ 2 BAR
OUTLET PRESSURE	30 MBAR
CONNECTIONS	• IN 1" F - OUT 1" 1/4 F (SKU 1200) • IN 1" F - OUT 1" 1/4 F (SKU 1205)
MATERIALS	• BODY AND COVER: DIE CASTING ALUMINUM ALLOY, ACCORDING TO EN 1706 STANDARD • FLANGE FITTING: ALUMINUM ALLOY, ACCORDING TO EN 1706 STANDARD • DIAPHRAGM AND SEALING ELEMENTS: NITRILE RUBBER CONFORMING TO EN 549



Low Pressure Regulator

SKU	MODEL	PRICE
00000001200	LOW PRESSURE REGULATOR MOD. 2402/L - IN 1" F OUT 1" 1/4 F - FLOW RATE 60 KG/H	€646.65 VAT EXCLUDED
00000001205	LOW PRESSURE REGULATOR MOD. 2402/F - IN 1" F OUT 1" 1/4 F - FLOW RATE 120 KG/H	€1584.15 VAT EXCLUDED

