



Catalogues and Products > Heating > High and Low Pressure Lpg Regulators for Civil-industrial Applications > **Low Pressure Regulator with Manual Reset**

LOW PRESSURE REGULATOR WITH MANUAL RESET

Model with maximum pressure block only valve and relief incorporated, flow rate 3 and/or 4 kg

Product informations

Low pressure regulator with manual reset for LPG with maximum pressure block only valve (OPSO) and relief valve incorporated, designed to make the gas pressure at the outlet of a tank suitable for the downstream user.

The regulator supplied with

- fixing support
- security seal
- nut and injector (to be installed)

Technical Features

TYPES OF GAS	LPG
FLOW RATE	• 3 KG - SKU 1689 • 4 KG - SKU 1690
OPERATING TEMPERATURE	- 20°C ÷ + 50°C



Low Pressure Regulator with Manual Reset

INLET PRESSURE	0,3 ÷ 16 BAR
OUTLET PRESSURE	• 37 MBAR - SKU 1689 • 29 MBAR - SKU 1690
CONNECTIONS	IN NUT W20LH-25-UNI OUT 1/2" F
MATERIALS	• BODY AND COVER: ZINC ALLOY (ZAMA) • DIAPHRAGM AND GASKETS: ELASTOMER COMPLIANT WITH EN549

SKU	MODEL	PRICE
00000001689	LOW PRESSURE REGULATOR - FLOW RATE 3 KG - IN NUT W20LH-25-UNI OUT 1/2" F	€160.0 VAT EXCLUDED
00000001690	LOW PRESSURE REGULATOR - FLOW RATE 4 KG - IN NUT W20LH-25-UNI OUT 1/2" F	€156.9 VAT EXCLUDED





Low Pressure Regulator with Manual Reset

