



Low Pressure Regulator with Manual Reset

Catalogues and Products > Riscaldamento > Regolatori Gpl Alta e Bassa Pressione per Applicazioni Civili-industriali > **Low Pressure Regulator with Manual Reset**

LOW PRESSURE REGULATOR WITH MANUAL RESET

Model with safety relief valve and min/max blocking device incorporated, flow rate 10,5 kg/h

Product informations

Low pressure regulator with safety relief valve and min/max block device incorporated, designed to make the gas pressure at the outlet of a tank suitable for the downstream user.

Technical Features

TYPES OF GAS	LPG
FLOW RATE	10,5 KG/H
OPERATING TEMPERATURE	- 20°C ÷ + 50°C
INLET PRESSURE	• 0,5 ÷ 2 BAR - SKU 1700 • 0,25 ÷ 2 BAR - SKU 1693
OUTLET PRESSURE	• 29 MBAR - SKU 1700 • 37 MBAR - SKU 1693
CONNECTIONS	• IN 1/2" F - OUT 1/2" F - SKU 1700 • IN LEFT NUT W20LH-25-UNI OUT 1/2" F - SKU 1693
LOCKING DEVICE	• OPSO 135 MBAR - UPSO < 25 MBAR - SKU 1700 • OPSO 125 MBAR - SKU 1693
MATERIALS	• BODY AND COVER: ZINC ALLOY (ZAMA) • DIAPHRAGM AND GASKETS: ELASTOMER COMPLIANT WITH EN549



Low Pressure Regulator with Manual Reset

SKU	MODEL	PRICE
00000001693	LOW PRESSURE REGULATOR - IN LEFT NUT W20LH-25-UNI OUT 1/2" F - FLOW RATE 10,5 KG/H	€163.15 VAT EXCLUDED
00000001700	LOW PRESSURE REGULATOR - IN 1/2" F - OUT 1/2" F - FLOW RATE 10,5 KG/H	€163.65 VAT EXCLUDED

