



Catalogues and Products > Heating > Lpg regulators for domestic use, high and low pressure > **Regulator with Automatic Reverse**

REGULATOR WITH AUTOMATIC REVERSE

Flow Rate 12 kg/h

Product informations

High pressure regulator with automatic reverser, designed to allow for priority gas withdrawal from the service cylinder and not to collect gas from the reserve one unless the one in service is no longer able to ensure the required gas supply; thus ensuring a continuous flow of gas without interrupting the service to the appliance and maximizing the quantity of gas available in the cylinders.

Equipped with two inlet connections with non-return valves that prevent gas from leak when changing the cylinder and filters that prevent entry of dirt.

Technical Features

TYPES OF GAS	LPG
FLOW RATE	12 KG/H
OPERATING TEMPERATURE	- 20°C ÷ + 50°C
INLET PRESSURE	2 ÷ 16 BAR
OUTLET PRESSURE	1,5 BAR
CONNECTION	IN MAL W20LH-UNI - OUT MAL W20LH-UNI



Regulator with Automatic Reverse

SKU	MODEL	PRICE
00000002600	REGULATOR WITH AUTOMATIC REVERSE - IN MAL W20LH-UNI OUT MAL W20LH-UNI - FLOW RATE 12 KG/H	€163.3 VAT EXCLUDED

