



HIGH PRESSURE REGULATOR

Model DIVAL 507 and 512

Product informations

High pressure regulator *Mod. DIVAL 507 and 512* equipped with incorporated safety relief valve and internal sensing line, to be used with previously filtered not corrosive gases.

Also available in the version with shut-off valve for maximum and minimum downstream pressure (*sku 2560B / 2570B*).

Technical Features

SKU	MODEL	FLOW RATE	CONNECTIONS	VENT VALVE DIAMETER	INLET PRESSURE	OUTPUT PRESSURE RANGE	STANDARD PRESSURE	ROOM TEMPERATURE	MATERIALS	DIMENSIONS
2560	DIVAL 507	60 KG/H - 50 M³/H	IN 1" F - OUT 1" F	Ø 1/4" F	18 BAR	0,3 ÷ 2 BAR	0,5 BAR	- 20°C ÷ + 50°C	• BODY: GS 400 CAST IRON • HEADER: ALUMINUM • SEAT: BRASS • MEMBRANE: RUBBER WITH FABRIC FINISH • O-RING: NITRILE RUBBER	100 X 190 X 49 X 185,5 MM (AXBXCXD)
2560B	DIVAL 507 WITH SHUT-OFF VALVE	60 KG/H - 50 M³/H								100 X 190 X 185 X 185,5 MM (AXBXCXD)
2570	DIVAL 512	120 KG/H - 100 M³/H	IN 1" F - OUT 1" 1/2 F							129 X 257 X 55 X 185,5 MM (AXBXCXD)
2570B	DIVAL 512 WITH SHUT-OFF VALVE	120 KG/H - 100 M³/H								129 X 194 X 185 X 185,5 MM (AXBXCXD)



High Pressure Regulator

SKU	MODEL	PRICE
00000002560	REGULATOR MOD. DIVAL 507 - IN 1" F - OUT 1" F	ON REQUEST
00000002570	REGULATOR MOD. DIVAL 512 - IN 1" F - OUT 1" 1/2 F	ON REQUEST
00000002560B	REGULATOR MOD. DIVAL 507 - IN 1" F - OUT 1" F - WITH SHUT-OFF VALVE	ON REQUEST
00000002570B	REGULATOR MOD. DIVAL 512 - IN 1" F - OUT 1" 1/2 F - WITH SHUT-OFF VALVE	ON REQUEST





High Pressure Regulator

