



Catalogues and Products > Heating > Methane Gas Regulators - Stabilizers for Civil and Industrial Applications > **Double Membrane Stabilizer without Filter**

DOUBLE MEMBRANE STABILIZER WITHOUT FILTER

FRG/2MT model, maximum pressure 500 mbar

Product informations

Device which supplies a preset and constant “downstream” pressure value, when the inlet pressure and/or the flow rate changes.

Equipped with

- spring for adjusting the output pressure
- safety membrane
- inlet and output pressure tap for output pressure control
- incorporated filter organ

Technical Features

<i>USE</i>	NOT AGGRESSIVE GASES OF THE THREE FAMILIES (MANUFACTURED / NATURAL / LPG)
<i>INLET PRESSURE RANGE</i>	400 ÷ 500 MBAR
<i>OUTPUT PRESSURE RANGE</i>	16 TO 60 MBAR
<i>FILTER SURFACE</i>	2810 MM ²
<i>FILTER ORGAN</i>	50 µM FILTRATION



Double Membrane Stabilizer without Filter

INLET CONNECTION	• 1/2" FF - SKU 40031 • 3/4" FF - SKU 40032 • 1" FF - SKU 40033
OUTPUT CONNECTION	• 1/2" FF - SKU 40031 • 3/4" FF - SKU 40032 • 1" FF - SKU 40033
PRESSURE TAP	ACCORDING TO UNI 8979
OPERATING TEMPERATURE	- 15°C ÷ + 60°C
MATERIAL	DIE-CAST ALUMINUM
DIMENSIONS	120 X 152 MM (AXB)

SKU	MODEL	PRICE
00000040031	DOUBLE DIAPHRAGM STABILIZER FRG/2MT MODEL - 1/2" FF CONNECTIONS	€64.9 VAT EXCLUDED
00000040032	DOUBLE DIAPHRAGM STABILIZER FRG/2MT MODEL - 3/4" FF CONNECTIONS	€63.65 VAT EXCLUDED
00000040033	DOUBLE DIAPHRAGM STABILIZER FRG/2MT MODEL - 1" FF CONNECTIONS	€66.8 VAT EXCLUDED

