



STANDARD BLUE KIT

The complete boiler-saver kit

Product informations

BLUE KIT STANDARD consists of the *MagBlue Mini* magnetic filter (SKU 70045), the *DosaBlue One* polyphosphate dispenser (SKU 70874), the Neutral Acid Water 35K neutralizing cartridge and the *LiquidBlue 100* anti-scaling anticorrosive liquid (SKU 70085).

Technical Features

SKU 70045	
MAXIMUM WORKING PRESSURE	10 BAR
WORKING TEMPERATURE	0 ÷ 90°C
LOAD LOSS	0,2 BAR
MAXIMUM HOURLY FLOW	1,3 M ³ /H
MAGNETIC FLUX DENSITY	12800 GAUSS
FILTRATION DEGREE	300 - 800 μM
MAGNET	NEODIMIO
CONNECTIONS	3/4"


Standard Blue Kit

SKU 70874	
90° CONNECTIONS	IN/OUT 1/2" <u>MOBILE</u>
MAX FLOW RATE	1,5 M ³ /H
MAX PRESSURE	3,5 BAR
WORKING TEMPERATURE	0°C - 45°C
RECHARGE AUTONOMY	12 - 15 M ³
PRESSURE DROP	0,2 BAR
VASE MATERIAL	SAN

SKU 70894	
VALID FOR BOILERS UP TO 35 KW	
LENGTH	220 MM
DIAMETER	47 MM
MAX PRESSURE	0,5 BAR
MAXIMUM TEMPERATURE	60°C
MAX CAPACITY	8 L/H
UNIT MATERIAL	PP
HOSE HOLDER MATERIAL	PP
MATERIAL FIXING SYSTEM	PP
NEUTRALIZING CHARGE IN CALCIUM CARBONATE (CaCO ₃)	
EPDM HYDRAULIC SEALS	


Standard Blue Kit

<i>SKU 70894</i>	
ACCESSORIES	• PAIR OF 3/4" STRAIGHT HOSE CONNECTORS • FIXING CLIP WITH Ø 50 MM SCREWS

<i>SKU 70085</i>	
CATEGORY	AUXILIARY CHEMICAL PRODUCT FOR WATER TREATMENT
APPLICATION	BIOCIDAL ANTI-CORROSION ANTISCALANT FOR CLOSED CIRCUITS
APPEARANCE	LIQUID
COLOR	AMBER
PH	6,8
RELATIVE DENSITY	1,06
WORKING TEMPERATURE	FROM 10°C TO 130°C
SOLUBILITY WATER	SOLUBILE
WATER COMPATIBILITY	• MAKE-UP WATERS WITH LIMITED HARDNESS LEAKS • MEDIUM HARD WATER • SOFTENED OR DEMINERALISED WATER
DOSAGE	IT CAN BE INTRODUCED INTO THE SYSTEM VIA THE DOSING PUMP, FEED TANK OR OTHER CONVENIENT POINT IN THE CIRCUIT. THE OPTIMAL DOSAGE FOR CORRECT SYSTEM PROTECTION IS <u>1 LITER FOR EVERY 100 LITERS OF WATER IN THE HEATING SYSTEM.</u>
1 L JUG (1 KG)	



Standard Blue Kit

SKU	MODEL	PRICE
00000070078	STANDARD BLUE KIT	€176.9 VAT EXCLUDED

