



## THERMAL DISCHARGE VALVE

ISPESL approved valve

### Product informations

Positive action thermal discharge valve, with manual reset and optical signal, ISPESL approved.

### Technical Features

| <i>SKU 70217</i>                                                    |                                                                                                                             |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| <i>CONNECTIONS</i>                                                  | Ø 1" 1/4                                                                                                                    |
| <i>CALIBRATION TEMPERATURE</i>                                      | 95°C                                                                                                                        |
| <i>DEGREE OF PROTECTION</i>                                         | IP40 (NOT PROTECTED AGAINST THE INGRESS OF LIQUIDS, PROTECTED THOUGH AGAINST THE INGRESS OF SOLID OBJECTS LARGER THAN 1 MM) |
| <i>DISCHARGE POTENTIAL WITHOUT RESTORATION</i>                      | 176,750 KCAL/H EQUAL TO 7070 L/H                                                                                            |
| <i>DISCHARGE TEMPERATURE</i>                                        | 96°C                                                                                                                        |
| <i>CLOSING TEMPERATURE</i>                                          | 92°C                                                                                                                        |
| <i>FLOW COEFFICIENT (<math>\Delta P=1</math> KG/CM<sup>2</sup>)</i> | 11.000 KG/H                                                                                                                 |



## Thermal Discharge Valve

| SKU 70218                                            |                                                                                                                             |
|------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| CONNECTIONS                                          | Ø 1" 1/2                                                                                                                    |
| CALIBRATION TEMPERATURE                              | 95°C                                                                                                                        |
| DEGREE OF PROTECTION                                 | IP40 (NOT PROTECTED AGAINST THE INGRESS OF LIQUIDS, PROTECTED THOUGH AGAINST THE INGRESS OF SOLID OBJECTS LARGER THAN 1 MM) |
| DISCHARGE POTENTIAL WITHOUT RESTORATION              | 318.200 KCAL/H EQUAL TO 12728 L/H                                                                                           |
| DISCHARGE TEMPERATURE                                | 96°C                                                                                                                        |
| CLOSING TEMPERATURE                                  | 90°C                                                                                                                        |
| FLOW COEFFICIENT ( $\Delta P=1$ KG/CM <sup>2</sup> ) | 20.000 KG/H                                                                                                                 |

| SKU         | MODEL                              | PRICE                |
|-------------|------------------------------------|----------------------|
| 00000070217 | THERMAL DISCHARGE VALVE - Ø 1" 1/4 | €793.6 VAT EXCLUDED  |
| 00000070218 | THERMAL DISCHARGE VALVE - Ø 1" 1/2 | €1145.1 VAT EXCLUDED |

