



THERMONET BOILERS

Disgregant for soot and incombustible deposits

Product informations

Disgregant for soot and unburnt deposits, formulated in powder form, suitable for all types of liquid fuel boilers (diesel, naphtha, kerosene, fuel oil) and usual (wood, coal); designed to remove corrosive incrustations and oxides, improving combustion and boiler efficiency, by acting on the most inaccessible points of the combustion chamber during the period of operation.

Product features

- combats corrosion from sulfur and corrosive agents present in diesel and fuel oils
- not suitable for wall-hung boilers operating on gas or methane
- the product gives maximum performance with the system in operation

Technical Features

APPEARANCE	CRYSTALLINE SOLID
COLOR	WHITE
FUSION POINT (1013 HPA)	335°C
PH	6 ÷ 9
SOLUBILITY IN WATER	> 100 G/L
WEIGHT	200 G



Thermonet Boilers

DOSAGE

- 1ST DAY - PUT IN CONTACT WITH THE OPEN FLAME N. 2 SMALL LOGS
- 2ND DAY - REPEAT THE OPERATION WITH A SINGLE SMALL LOG
- TO KEEP YOUR BOILER OR FIREPLACE EFFICIENT AND CLEAN, REPEAT THE OPERATION EVERY 15 - 20 DAYS

SKU	MODEL	PRICE
00000070789	THERMONET BOILERS - 200 G	€15.4 VAT EXCLUDED

