



Catalogues and Products > Heating > Methane/lpg Regulators for Civil - Industrial Applications > **Medium Pressure Regulator**

MEDIUM PRESSURE REGULATOR

Alfa 10 MP series, with balanced direct action regulation

Product informations

Alfa 10 MP series regulator with balanced direct action, equipped with external sensing line and safety relief valve; suitable for the use of not corrosive gases as methane and LPG.

Also available the version with minimum and maximum pressure shut-off valve downstream (sku 2416).

REGULATOR STRUCTURE	
1	O-RING
2	O-RING
3	O-RING
4	O-RING
5	O-RING
6	O-RING
7	O-RING
8	O-RING
9	O-RING
10	MEMBRANE



Medium Pressure Regulator

REGULATOR STRUCTURE	
11	PILL
12	LIP RING
13	BALANCING MEMBRANE
A	PLASTIC CAP + O-RING
B	COMPLETE HEADER
C	FULL LEVERAGE
D	COMPLETE BLOCK
E	SHUTTER SEAT + O-RING
F	BOTTOM PLATE + O-RING + SCREWS
G	MEMBRANE PROTECTIVE PLATE
H	• BLUE SPRING Ø 2,5 (SETTING 95 ÷ 130 MBAR) • ORANGE SPRING Ø 3 (SETTING 130 ÷ 220 MBAR) • BROWN SPRING Ø 3,5 (SETTING 200 ÷ 300 MBAR) • PURPLE SPRING Ø 3,5 (SETTING 260 ÷ 450 MBAR)
I	ADJUSTMENT FERRULE

Technical Features

FLOW RATE	SEE TABLE UNDERLYING
INLET CONNECTION	1"
OUTPUT CONNECTION	1"
INLET PRESSURE	0,5 ÷ 5 BAR
OUTPUT PRESSURE	95 ÷ 450 MBAR
STANDARD OUTPUT PRESSURE	ON REQUEST



Medium Pressure Regulator

WORKING TEMPERATURE	- 20°C ÷ + 60°C
EXTERNAL SENSING LINE	Ø 10
MATERIALS	• BODY: GS 400 CAST IRON • HEADER: DIE-CAST ALUMINIUM • SEAL: NITRILE RUBBER NBR OR HNBR • MEMBRANE: SANDWICH RUBBERIZED FABRIC
DIMENSIONS	180 X 100 X 50 MM

	INLET PRESSURE		
	0,5 BAR	1 BAR	1,5 BAR
OUTLET PRESSURE	0,11 BAR	63 M ³ /H	91 M ³ /H
	0,15 BAR	57 M ³ /H	87 M ³ /H
	0,20 BAR	47 M ³ /H	82 M ³ /H
	0,30 BAR	-	70 M ³ /H

To obtain the LPG flow rates in kg/h, multiply the values in red by 1,42.

SKU	MODEL	PRICE
00000002414	ALFA 10 MP SERIES REGULATOR - 1"X1" CONNECTION	€565.6 VAT EXCLUDED
00000002416	ALFA 10 MP SERIES REGULATOR - 1"X1" CONNECTION - WITH BLOCK	€963.6 VAT EXCLUDED



Medium Pressure Regulator

