



## LPG WATER VAPORIZER

Feed-Out type, flow rate 100 and/or 200 kg/h

### Product informations

Water LPG vaporizer *mod. Feed-Out*, designed to transform liquefied gas at the inlet, to a gaseous state at the outlet in maximum safety, ready to be used in civil, industrial and commercial systems; this vaporizer works in open cycle with the powered system, equipped with mechanical control of the liquid level inside and with the possibility of liquid return to the tank in case of overpressure.

### *Vaporizer equipped with*

- pressure gauge
- safety valve
- thermometer
- filter
- ball valve
- water safety valve
- vent release valve

### Technical Features

|                    |       |
|--------------------|-------|
| <b>GAS INLET</b>   | DN 15 |
| <b>GAS OUTLET</b>  | DN 25 |
| <b>WATER INLET</b> | Ø 1"  |



## LPG Water Vaporizer

|                                   |                                                                                                                        |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>WATER OUTLET</b>               | Ø 1"                                                                                                                   |
| <b>PRESSURE GAUGE</b>             | Ø 60 MM - SETTING 25 BAR                                                                                               |
| <b>SAFETY VALVE</b>               | Ø 1/2" - SETTING 18 BAR                                                                                                |
| <b>THERMOMETER</b>                | - 20°C ÷ + 120°C                                                                                                       |
| <b>BALL VALVE</b>                 | DN 15 - PN 40                                                                                                          |
| <b>WATER SAFETY VALVE SETTING</b> | 1,5 BAR                                                                                                                |
| <b>PROJECT TEMPERATURE</b>        | - 40°C ÷ + 120°C                                                                                                       |
| <b>PROJECT PRESSURE</b>           | 40 BAR                                                                                                                 |
| <b>FLOW RATE</b>                  | <ul style="list-style-type: none"> <li>• 100 KG/H - <b>SKU 50097</b></li> <li>• 200 KG/H - <b>SKU 50098</b></li> </ul> |

| <b>DIMENSIONS</b> |          |          |          |          |          |
|-------------------|----------|----------|----------|----------|----------|
| <b>SKU</b>        | <b>A</b> | <b>B</b> | <b>C</b> | <b>D</b> | <b>E</b> |
| 50097             | 1330 MM  | 560 MM   | 420 MM   | 150 MM   | 300 MM   |
| 50098             | 1330 MM  | 560 MM   | 420 MM   | 150 MM   | 300 MM   |

| <b>SKU</b>  | <b>MODEL</b>                                            | <b>PRICE</b>         |
|-------------|---------------------------------------------------------|----------------------|
| 00000050097 | WATER LPG VAPORIZER FEED-OUT MODEL - FLOW RATE 100 KG/H | €4440.9 VAT EXCLUDED |
| 00000050098 | WATER LPG VAPORIZER FEED-OUT MODEL - FLOW RATE 200 KG/H | €4964.6 VAT EXCLUDED |



## LPG Water Vaporizer

