



LPG WATER VAPORIZER

Feed-Out type, flow rate 300 and/or 500 kg/h

Product informations

Water LPG vaporizer *mod. Feed-Out*, designed to transform liquefied gas at the inlet, to a gaseous state at the outlet in maximum safety, ready to be used in civil, industrial and commercial systems; this vaporizer works in open cycle with the powered system, equipped with mechanical control of the liquid level inside and with the possibility of liquid return to the tank in case of overpressure.

Vaporizer equipped with

- pressure gauge
- safety valve
- thermometer
- filter
- ball valve
- water safety valve
- vent release valve

Technical Features

GAS INLET	• DN 15 - SKU 50099 • DN 25 - SKU 50100
GAS OUTLET	• DN 25 - SKU 50099 • DN 40 - SKU 50100
WATER INLET	Ø 1"



LPG Water Vaporizer

WATER OUTPUT	Ø 1"
MANOMETER	Ø 60 MM - SETTING 25 BAR
SAFETY VALVE	Ø 1/2" - SETTING 18 BAR
THERMOMETER	- 20°C ÷ + 120°C
BALL VALVE	• DN 15 - PN 40 (SKU 50099) • DN 25 - PN 40 (SKU 50100)
WATER SAFETY VALVE SETTING	1,5 BAR
PROJECT TEMPERATURE	- 40°C ÷ + 120°C
PROJECT PRESSURE	40 BAR
FLOW RATE	• 300 KG/H -SKU 50099 • 500 KG/H -SKU 50100

DIMENSIONS				
SKU	A	B	C	D
50099	1330 MM	620 MM	310 MM	300 MM
50100	1660 MM	620 MM	445 MM	300 MM

SKU	MODEL	PRICE
00000050099	WATER LPG VAPORIZER FEED-OUT MODEL - FLOW RATE 300 KG/H	€6409.95 VAT EXCLUDED
00000050100	WATER LPG VAPORIZER FEED-OUT MODEL - FLOW RATE 500 KG/H	€7478.3 VAT EXCLUDED



LPG Water Vaporizer

