



Catalogues and Products > Heating > Meters for Water > **Whirlpool Meter**

WHIRLPOOL METER

Removable drum axial woltmann meter

Product informations

Woltmann meter with epoxy powder coated cast iron body, direct reading on numbered rolls and ring that can be rotated at 360°C.

Product features

- for use with irrigation water (even unfiltered with small suspended bodies) and for the industrial sector
- with magnetic drive transmission
- pressure drops reduced to a minimum, thanks to the free flow meter
- removable and interchangeable measuring group
- temperature class T30
- possibility of horizontal, vertical or inclined installation
- metal lid with the possibility of closing with a padlock
- MID homologated
- Temperature range: -15°C÷+55°C

Technical Features



Whirlpool Meter

SKU	DIAMETER (MM)	PERMANENT FLOW RATE Q_3 (M ³ /H)	OVERLOAD FLOW RATE Q_4 (M ³ /H)	MINIMUM FLOW RATE Q_1 [MPE $\pm 5\%$] (M ³ /H)	MINIMUM READING UNIT (L)
70550	Ø 50 MM	63	78,75	0,63	0,5
70551	Ø 65 MM	63	75,75	0,63	0,5
70552	Ø 80 MM	100	125	1	0,5
70553	Ø 100 MM	160	200	1,6	5
70554	Ø 150 MM	250	312,5	2,5	5

SKU	MODEL	PRICE
00000070550	WHIRLPOOL METER - L. 200 MM - DN 50	€673.65 VAT EXCLUDED
00000070551	WHIRLPOOL METER - L. 200 MM - DN 65	€757.9 VAT EXCLUDED
00000070552	WHIRLPOOL METER - L. 225 MM - DN 80	€808.65 VAT EXCLUDED
00000070553	WHIRLPOOL METER - L. 250 MM - DN 100	€943.75 VAT EXCLUDED
00000070554	WHIRLPOOL METER - L. 300 MM - DN 150	€1485.45 VAT EXCLUDED

